



Starkstrom

Room Status Luminaire

**Product Ref.:**

- IUS1010-010

Configuration:

- Single Channel

Electrical:

- Input Voltage: 230-240VAC $\pm 10\%$
- Input Frequency: 50-60Hz
- Input Current: $< 100\text{mA}$
- Internal 1.0A Fuse
- MEIGaN Compliant Earthing

Lamp Type:

- 1x8W T5 Fluorescent
- Mains HF Only

Environmental:

- Operating Temp. Range: $0^{\circ}\text{C} - 30^{\circ}\text{C}$
- Ingress Protection: IP30

Enclosure:


- Steel, Powder Coated RAL9001
- Flush Wall Mounting

Relevant Standards:

- EN60598-1, EN60555-2, EN50082-1, EN55015, CE Marked

Dimensions:

- Overall Size: 355w x 105h x 74d x 2kg
- Wall Recess Size: 334w x 87h x 65d
- 20mm Conduit Knockouts x2

**Typical Legends Available:**

- In-Use
- Room In-Use
- Theatre In-Use
- Laser On
- Laser In-Use
- Caution
- Protected Area
- Mains On
- X-Ray On
- X-Ray In-Use
- Do Not Enter
- Engaged
- Controlled Area
- Lecture in Progress
- Meeting in Progress
- Any Custom Legend (Upon Request)

